



Product

Form-Flex® Floating Shaft

Application

Power Plant Induced Draft Fans

Highlights

- Engineered solution for a retrofit application
- 21.5 ft. long coupling with an oversized tube diameter (24 in.) to meet torsional requirements
- Modified for limited end float
- 1,100,000 lb.in. continuous torque capacity
- 4140 alloy steel motor hub, carbon steel fan adapter and spacer with stainless steel disc packs
- Special adapter connects directly to fan drive flange

A major global industrial fan OEM needed a replacement coupling solution for an induced draft fan drive at a large power plant. The fan maintains system pressure slightly below atmospheric pressure on a coal-fired boiler at the facility. The existing fan drive used an old gear coupling design which had reached the end of its useful life.

The OEM contacted TB Wood's based on many previous successful collaborations. The customer requested a disc coupling solution since they wanted to increase expected service life and eliminate the need for lubrication. TB Wood's engineers recommended switching to a Form-Flex floating shaft coupling to mount between the drive motor and the fan.

The custom coupling was modified with limited end float features to keep the sleeve bearing motor rotor from being damaged. The large 21.5 ft. long coupling is being used for an operating speed of 600 RPM, but the first critical speed is much higher due to the oversized tube diameter (24 in.) to meet the torsional requirements of the fan drive system.

The Form-Flex floating shaft has a continuous torque capacity of 1,100,000 lb.in. with a peak torque rating of 2,400,000 lb.in. The robust coupling design features an alloy steel motor hub with provisions for hydraulic removal, carbon steel flange adapter, welded steel spacer, high-strength alloy steel hardware and stainless steel disc packs.

The new coupling required a shaft hub connection at the motor end and a special adapter flange on the fan end to mate with the existing fan flange. Since this was a retrofit application, axial adjustment shims were provided so the customer could fine tune the coupling spacing on the job site.

US (Application Assistance)
1-888-829-6637 press #7
tbwoods.com

Asia Pacific
For a list of our AP sales offices:
altramotion.com/contactus